



FiberFlex® Maintenance and Cleaning Instructions

FiberFlex® is easy to clean and you can use any commercially available cleaner without impacting your product warranty. The inherent chemical resistant properties that are present gives maintenance providers a wider usable range of cleaners or disinfectants than weaker compounds allow. Traditional floor cleaning protocols are acceptable including but not limited to ammonia water solutions and cleaning products in a 7 to 10 ph range. Brushing and scrubbing FiberFlex® with traditional nylon bristle scrub brushes are proper and effective ways to remove loose dirt and stains.

Below is our recommended cleaning process.

Cleaning Tools:

- ✚ Wet Floor Sign
- ✚ Broom and Dustpan
- ✚ Cleaning Bucket
- ✚ Deck Brush or Power Scrubber
- ✚ Squeegee
- ✚ Hot Water
- ✚ Commercial Cleaner

Cleaning Process

1. Display wet floor sign(s) to maintain safety.
2. Thoroughly sweep area to be cleaned and remove debris.
3. Mix your commercial flooring cleaner **according to manufacturer's recommendations** and add to cleaning bucket.
4. Apply cleaning mixture to floor and ensure full coverage.
5. Firmly brush the entire floor
6. Brush liquid to the nearest drain. Use a wet vacuum if no drains are present.
7. Complete with a final fresh, hot water rinse. Brush liquid to the nearest drain. Use a wet vacuum if no drains are present.

Do NOT use undiluted bleach on FiberFlex®. Undiluted sodium hypochlorite will lead to permanent staining.